


624/1
-------

ITEM NO.	PART NUMBER	DESCRIPTION	Material	Finish	QTY.
1	62471_Swivel Hook	1/2" Swivel Hook	Steel	Zinc	1
2	62471 Swivel Pin	Swivel Retaining Pin	Steel	Zinc	1
3	62471 MAGNET CUP	Ø1.42" (36mm) Magnet Cup Ø.250" (6.35mm) Hole	MILD STEEL	ZINC	1
4	62471 MAGNET	Ø1.065" (27mm) Ring Magnet	NdFeB N35M	NiCuNi	1
5	Seal		Nylon		1
6	Retainer RIng	Side-Mount External Retaining Ring	1060-1090 Spring Steel	Zinc	1







## **Mechanical Tensile Strength:**

Vertical Pull 75 LBS. (333N)

Side Pull 10 LBS. (44N)

ALL TESTING PERFORMED USING
3mm MIN. THICK 1008-1010 STEEL PLATE


Vertical Pull
Direction
Side Pull
Direction

Please read before use! Disclaimer: Mag Daddy neither assumes nor accepts any liability for damages resulting from the handling or use of magnets. With your purchase, the buyer confirms that you have read and understand the following warnings: the buyer agrees that he/she is responsible for all damages/injuries caused by the magnets, which includes personal injuries, property damages or magnet damages. The buyer must agree with the terms before purchase. Pull forces we have provided are estimates only, we are not responsible for any inaccuracy of the magnet pull force. Please test the pull force before any usage. Magnets are very strong. Handling them with care is necessary to prevent personal injuries, property damages and magnet damages.

CAN BE HARMFUL TO PACEMAKER WEARERS and others with MEDICAL IMPLANTS.

## INDOOR USE RECOMMENDED

OPERATING TEMPERATURE - -40° - 176° F (-40°- 80°C)



75lb.(333N) Swivel Hook Magnet

62471

LAST PRINT DATE: 10/13/2024